



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2000294831 A**(43) Date of publication of application: **20.10.2000**

(51) Int. Cl. **H01L 33/00**
H01L 31/12

(21) Application number: **11101894**(22) Date of filing: **08.04.1999**(71) Applicant: **OMRON CORP**

(72) Inventor: **YANAGASE MASASHI**
KONISHI YASUHIRO
IMAMOTO HIROSHI
TAKAOKA MOTOAKI
YAMA YOSHIKAZU

(54) **SEMICONDUCTOR LIGHT EMITTING DEVICE,
 ARRAY THEREOF, PHOTSENSOR, AND
 PHOTSENSOR ARRAY**

53 after the light is enclosed in the cavity 50 by the reflecting film 54 which reflects the light.

COPYRIGHT: (C)2000,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To obtain a high-luminance high-output semiconductor light emitting device.

SOLUTION: On a glass substrate 42, an LED chip 45 is mounted and a structure 47 is provided around the chip 45. The structure 47 is formed of two semiconductor substrates 48 and 49, and a reflecting film 54 composed of Au, etc., is provided on the internal surface of a cavity 50. On the top face of the structure 47, a small light emitting port 53 is provided. The light emitted from the LED chip 45 is emitted from the port

